

PHL POWDER HOPPER LOADER



PHL-50 Powder Hopper Loader

PHL STANDARD FEATURES

- Stainless steel SR-style vacuum receiver
- Counter-weighted flapper assembly
- Twin bag filter assembly
- High flow blowback valve with accumulator and electrical quick disconnect
- 1.5" OD tangential material inlet
- Hopper-mounted junction box
- Remote control box with 10 foot cable
- Material demand/level sensor
- High-performance three-stage centrifugal motor with electrical quick disconnect
- 9-foot power cord
- Series One controller
- Dual tube aluminum pick-up wand with 10 feet of vinyl hose and 2 hose clamps
- Sound enclosure

Options

- 230/1/50 or 60 Supply Voltage

Quiet, Efficient Operation Easy Cleanout Design Heavy-Duty Construction

ACS Group • Walton/Stout PHL Powder Hopper Loaders are used to convey free-flowing powder materials like PVC and PE from gaylords to machine hoppers, blenders, or surge bins.



BLOWBACK VALVE

Accumulator Blow-back with large solenoid for maximum filter cleaning of dual bag filter assembly.



DUAL BAG FILTER

Dual bag filter assembly efficiently traps fines and dust.



SERIES 1 CONTROLLER

On/off operator control with visual indicator. Adjustable time filling provides up to 1,000 lbs./hr.

ACS Group • Walton/Stout is committed to a continuing program of product improvement. Dimensions are subject to change without notice.

© 2009 ACS Group • Walton/Stout

Bulletin WMH4-120

Printed in USA

WS

ACS GROUP • WALTON/STOUT

ACS Group • Walton/Stout
2900 S. 160th Street
New Berlin, WI 53151

Phone: 262-641-8600
Fax: 262-641-8653
Email: waltonstout@waltonstout.com

www.waltonstout.com